



Part Number : 465567145

Series Number : 46556

Product Category : Board-to-Board  
Connectors

Product Description : Searay Slim Plug, 100  
Circuits, 2.00mm Unmated Height, 4 Rows,  
with Pegs, Solder Charge Lead-Free

Status : Active

## Documents & Resources

### Drawings

Drawing 465567145\_sd.pdf  
Packaging Design Drawing PK-45970-002-001.pdf

### 3D Models and Design Files


3D Model 465567145\_stp.zip  
Electrical Model Document EE-45970-010-010.pdf  
S-Parameter Model SP-45970-010-010.zip  
Symbol Footprint Data SYM-46556-7145-001.zip

### Specifications

Application Specification AS-45970-001-001.pdf  
Application Specification AS-45970-002-001.pdf  
Application Specification AS-45970-990-001.pdf  
Product Specification PS-45970-001-001.pdf  
Product Specification TS-45970-001-001.pdf  
Test Summary TS-45970-002-001.pdf

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS

- REACH SVHC

- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D

- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

#### EU RoHS Certificate of Compliance

---

## Part Details

### General

Status	Active
Category	Board-to-Board Connectors
Series	46556
Description	Searay Slim Plug, 100 Circuits, 2.00mm Unmated Height, 4 Rows, with Pegs, Solder Charge Lead-Free
Application	Board-to-Board, Signal
Component Type	PCB Header
Product Family	SEARAY and SEARAY Slim Mezzanine Family
Product Name	SEARAY
UPC	800756931678

### Agency

CSA	LR19980
UL	E29179

### Electrical

Current - Maximum per Contact	2.7A
Voltage - Maximum	240V AC

### Physical

Breakaway	No
Circuits (Loaded)	100
Circuits (maximum)	100

Color - Resin	Black
Durability (mating cycles max)	100
First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	Yes
Keying to Mating Part	Yes
Lock to Mating Part	None
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	1.419/g
Number of Rows	4
Orientation	Vertical
Packaging Type	Embossed Tape on Reel
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Pitch - Mating Interface	1.27mm
Pitch - Termination Interface	1.27mm
Plating min - Mating	0.762µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Robotic Placement	Pick and Place Cap
Shrouded	No
Stackable	No
Temperature Range - Operating	-55° to +125°C
Termination Interface Style	Surface Mount
Unmated Height	2.00mm

## Solder Process Data

Max-Duration	20
Lead-Free Process Capability	REFLOW
Max-Cycle	3

Max-Temp	260
----------	-----

---

Mates With / Use With

Mates with Part(s)

Description	Part Number
SEARAY Slim Receptacles	<u>46557</u>