



Part Number : [529910808](#)

Series Number : 52991

Product Category : Board-to-Board
Connectors

Product Description : 0.50mm Pitch SlimStack
Receptacle, Surface Mount, Dual Row,
Vertical, 3.00 and 4.00mm Stacking Heights,
Lower Circuit Size Version, White, 80 Circuits

Status : Active

Documents & Resources

Drawings

[Drawing 529910808_sd.pdf](#)

3D Models and Design Files

[3D Model 529910808_stp.zip](#)

Specifications

[Packaging Specification 529919200-SPK-200.pdf](#)

[Product Specification 529910000-PS-000.pdf](#)

[Product Specification PS-52991-003-001.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Compliant with Exemption 44; 33
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

[Multiple Part Product Compliance Statements](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen

[Multiple Part Industry Compliance Documents](#)

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Board-to-Board Connectors
Series	52991
Description	0.50mm Pitch SlimStack Receptacle, Surface Mount, Dual Row, Vertical, 3.00 and 4.00mm Stacking Heights, Lower Circuit Size Version, White, 80 Circuits
Series Name	0.5, BB H3/4
Application	Board-to-Board, Signal
Component Type	PCB Receptacle
Product Family	SlimStack Board-to-Board/Board-to-FPC Connectors
Product Name	SlimStack
UPC	800754364522

Agency

UL	E29179
----	--------

Electrical

Current - Maximum per Contact	0.5A
Voltage - Maximum	50V

Physical

Circuits (Loaded)	80
Circuits (maximum)	80
Glow-Wire Capable	No
Mated Height	3.00mm, 4.00mm
Mated Width	5.40mm
Material - Plating Mating	Gold

Material - Plating Termination	Gold
Net Weight	336.569/mg
Number of Rows	2
Orientation	Vertical
Packaging Type	Embossed Tape on Reel
PCB Locator	No
PCB Retention	None
PCB Thickness - Recommended	1.60mm
Pitch - Mating Interface	0.50mm
Plating min - Mating	0.102µm
Plating min - Termination	0.254µm
Polarized to PCB	No
Temperature Range - Operating	-40° to +105°C
Termination Interface Style	Surface Mount

Mates With / Use With

Mates with Part(s)

Description	Part Number
0.50mm Pitch SlimStack Board-to-Board Vertical Stacking Plugs	<u>501920</u>
0.50mm Pitch Vertical SlimStack Plugs	<u>53748</u>
0.50mm Pitch Vertical SlimStack Plugs	<u>53916</u>