

Part Number: 714360864

Product Description: 1.00mm Mezz (IEEE 1386) Plug, Surface Mount, Dual Row, Vertical Stacking, 64 Circuits, 6.35mm Unmated Height, without PCB Locator Pegs, with Robotic Placement Metal Cap, Embossed Tape on Reel Packaging

Tape of Recire

Status: Active

Series Number: 71436

**Product Category:** Board-to-Board

Connectors

#### **Documents & Resources**

#### **Drawings**

<u>Drawing 714360864\_sd.pdf</u> Packaging Design Drawing PK-70873-063-001.pdf

# 3D Models and Design Files

3D Model 714360864\_stp.zip

#### **Specifications**

Product Specification PS-71436-9999-001.pdf

### **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Compliant with Exemption 44                       |
|--------------------|---|
| China RoHS         | <b>©</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Not Contained per D(2023)8585-DC<br>(23 Jan 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

## Part Details

#### General

| Status         | Active  |
|----------------|---|
| Category       | Board-to-Board Connectors   |
| Series         | 71436   |
| Description    | 1.00mm Mezz (IEEE 1386) Plug,<br>Surface Mount, Dual Row, Vertical<br>Stacking, 64 Circuits, 6.35mm<br>Unmated Height, without PCB<br>Locator Pegs, with Robotic<br>Placement Metal Cap, Embossed<br>Tape on Reel Packaging |
| Application    | Board-to-Board, Signal  |
| Component Type | PCB Header  |
| Product Family | 1.00mm Mezzanine (IEEE 1386)  |
| Product Name   | 1.00mm Mezzanine (IEEE 1386)  |
| UPC            | 800754349826  |

## Agency

| CSA | LR19980 |
|-----|---------|
| UL  | E29179  |

### Electrical

| Current - Maximum per Contact | 1.0A |
|-------------------------------|------|
| Voltage - Maximum             | 100V |

## Physical

| Breakaway          | No      |
|--------------------|---------|
| Circuits (Loaded)  | 64      |
| Circuits (maximum) | 64      |
| Color - Resin      | Natural |
| Flammability       | 94V-0   |

| Glow-Wire Capable              | No                             |
|--------------------------------|--------------------------------|
| Lock to Mating Part            | None                           |
| Mated Height                   | 8.00mm                         |
| Material - Metal               | Phosphor Bronze                |
| Material - Plating Mating      | Gold                           |
| Material - Plating Termination | Tin                            |
| Material - Resin               | High Temperature Thermoplastic |
| Net Weight                     | 1.100/g                        |
| Number of Rows                 | 2                              |
| Orientation                    | Vertical                       |
| Packaging Type                 | Embossed Tape on Reel          |
| PCB Locator                    | No                             |
| PCB Retention                  | None                           |
| PCB Thickness - Recommended    | 1.00mm                         |
| Pitch - Mating Interface       | 1.00mm                         |
| Plating min - Mating           | 0.762µm                        |
| Plating min - Termination      | 1.905µm                        |
| Polarized to Mating Part       | No                             |
| Robotic Placement              | Pick and Place Cap             |
| Shrouded                       | Fully                          |
| Stackable                      | No                             |
| Temperature Range - Operating  | -55° to +85°C                  |
| Termination Interface Style    | Surface Mount                  |

### **Solder Process Data**

| Lead-Free Process Capability | REFLOW |
|------------------------------|--------|
| Max-Temp                     | 260    |

## Mates With / Use With

## Mates with Part(s)

| Description                                     | Part Number  |
|---|--------------|
| 1.00mm Mezz (IEEE 1386) Vertical<br>Receptacles | <u>71439</u> |

This document was generated on Apr 22, 2024