

Part Number : 716607030

**Product Description :** 1.27mm Pitch EBBI 50D Receptacle, Vertical, Blind Mate, 30 Circuits

Status: Active

Series Number: 71660

**Product Category: PCB Headers and** 

Receptacles

#### **Documents & Resources**

#### **Drawings**

<u>Drawing 716607030\_sd.pdf</u> Packaging Design Drawing PK-71660-001.pdf

### 3D Models and Design Files

3D Model 716607030\_stp.zip

## **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | •   |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                    |
| REACH SVHC         | Not Contained per D(2023)8585-DC<br>(23 Jan 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

#### **Multiple Part Product Compliance Statements**

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### EU RoHS Certificate of Compliance

# **Part Details**

### General

| Status         | Active   |
|----------------|--|
| Category       | PCB Headers and Receptacles  |
| Series         | 71660  |
| Description    | 1.27mm Pitch EBBI 50D Receptacle,<br>Vertical, Blind Mate, 30 Circuits |
| Application    | Board-to-Board, Signal   |
| Component Type | PCB Receptacle   |
| Product Family | EBBI 50D Connector System  |
| Product Name   | EBBI   |
| UPC            | 800754351522   |

# Agency

| CSA | LR19980 |
|-----|---------|
| UL  | E29179  |

## Electrical

| Current - Maximum per Contact | 1.0A |
|-------------------------------|------|
| Voltage - Maximum             | 30V  |

# Physical

| Circuits (Loaded)              | 30                             |
|--------------------------------|--------------------------------|
| Circuits (maximum)             | 30                             |
| Color - Resin                  | Black                          |
| Durability (mating cycles max) | 2000                           |
| Flammability                   | 94V-0                          |
| Glow-Wire Capable              | No                             |
| Material - Metal               | Phosphor Bronze                |
| Material - Plating Mating      | Gold                           |
| Material - Plating Termination | Tin                            |
| Material - Resin               | High Temperature Thermoplastic |
| Net Weight                     | 1.788/g                        |
| Number of Rows                 | 2                              |

| Orientation                   | Vertical       |
|-------------------------------|----------------|
| Packaging Type                | Tray           |
| PC Tail Length                | 2.79mm         |
| PCB Locator                   | Yes            |
| PCB Retention                 | Yes            |
| PCB Thickness - Recommended   | 2.79mm         |
| Pitch - Mating Interface      | 1.27mm         |
| Plating min - Mating          | 0.762µm        |
| Plating min - Termination     | 0.254µm        |
| Polarized to PCB              | Yes            |
| Temperature Range - Operating | -40° to +105°C |
| Termination Interface Style   | Through Hole   |

## **Solder Process Data**

| Lead-Free Process Capability | SMC&WAVE |
|------------------------------|----------|
| Max-Temp                     | 260      |

### Mates With / Use With

### Mates with Part(s)

| Description  | Part Number |
|--|-------------|
| 1.27mm Pitch EBBI 50D Plug,<br>Vertical, Blind Mate, 30 Circuits,<br>2.79mm PC Tail Length | 716617030   |

This document was generated on Apr 22, 2024