



Part Number : 2074200081

Series Number : 207420

Product Category : Board-to-Board  
Connectors

Product Description : SlimStack Board-to-Board Connector, 0.80mm Pitch, Battery Series, Plug, 0.75mm Mated Height, 2.50mm Mated Width, 8 Circuits, 11.0A

Status : Active

## Documents & Resources

### Drawings

Drawing 2074200081\_sd.pdf

### 3D Models and Design Files

3D Model 2074200081\_stp.zip


### Specifications

Packaging Specification 2074209400-400.pdf

Product Specification 2074190080-001.pdf

## Product Environment Compliance

### Compliance

GADSL/IMDS	Compliant with Exemption 34; 33; 44
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2023)8585-DC (23 Jan 2024)
EU RoHS	Compliant per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

## EU RoHS Certificate of Compliance

---

### Part Details

#### General

Status	Active
Category	Board-to-Board Connectors
Series	207420
Description	SlimStack Board-to-Board Connector, 0.80mm Pitch, Battery Series, Plug, 0.75mm Mated Height, 2.50mm Mated Width, 8 Circuits, 11.0A
Series Name	11A, Battery
Application	Board-to-Board
Comments	11A of current per circuit is applicable if the circuit was constructed by two power pins via a PWB/FPC circuit
Component Type	PCB Header
Product Family	SlimStack Board-to-Board/Board-to-FPC Connectors
Product Name	SlimStack
UPC	193264101238

#### Electrical

Current - Maximum per Contact	0.3A, 5.5A*
Voltage - Maximum	50V AC (RMS)/DC

#### Physical

Breakaway	No
Circuits (Loaded)	8
Circuits (maximum)	8
Color - Resin	Black
Durability (mating cycles max)	10
Glow-Wire Capable	No

Lock to Mating Part	Yes
Mated Height	0.75mm
Mated Width	2.50mm
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Material - Resin	Liquid Crystal Polymer
Net Weight	195.488/mg
Number of Rows	2
Orientation	Vertical
Packaging Type	Embossed Tape on Reel
PCB Locator	No
PCB Retention	Yes
Pitch - Mating Interface	0.80mm
Pitch - Termination Interface	0.80mm
Plating min - Mating	0.100µm
Plating min - Termination	0.050µm
Polarized to Mating Part	No
Polarized to PCB	No
(p)ower-(s)ignal Configuration	4p - 4s
Temperature Range - Operating	-40° to +85°C
Termination Interface Style	Surface Mount

---

## Mates With / Use With

### Mates with Part(s)

Description	Part Number
0.80mm Pitch SlimStack Board-to-Board Receptacles	<u>207419</u>