

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE				
△					△								
△					△								
APPLICATION STANDARD													
RATING	OPERATING TEMPERATURE RANGE	-55 °C TO 85 °C			STORAGE TEMPERATURE RANGE		-10 °C TO 60 °C						
	VOLTAGE	AC 50 V			OPERATING HUMIDITY RANGE		RELATIVE HUMIDITY : 95 % MAX (NO DEW CONDENSATION IS PERMITTED)						
	CURRENT	0.3 A											
SPECIFICATIONS													
ITEM		TEST METHOD			REQUIREMENT			QT/AT					
CONSTRUCTION													
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING			X X					
MARKING		CONFIRMED VISUALLY.						X X					
ELECTRICAL CHARACTERISTICS													
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz).			70 mΩ MAX.			X X					
INSULATION RESISTANCE		100 V DC.			100 MΩ MIN.			X —					
VOLTAGE PROOF		150 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			X X					
MECHANICAL CHARACTERISTICS													
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.			INSERTION FORCE: 60 N MAX WITHDRAWAL FORCE: 2.5 N MIN.			X —					
MECHANICAL OPERATION		50 TIMES INSERTION AND EXTRACTIONS.			1)CONTACT RESISTANCE: 80 mΩ MAX. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.			X —					
VIBRATION		FREQUENCY: 10 TO 55 Hz, SINGLE AMPLITUDE: 0.75 mm, — m/s ² AT 10 CYCLES FOR 3 DIRECTIONS.			1)NO ELECTRICAL DISCONTINUITY OF 1 μs MIN. 2)NO DAMAGE, CRACK AND LOOSENESS OF PART.			X —					
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.						X —					
ENVIRONMENTAL CHARACTERISTICS													
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90~95 %, 96 h.			1)CONTACT RESISTANCE: 80 mΩ MAX. 2)INSULATION RESISTANCE: 100 MΩ MIN.			X —					
RAPID CHAGE OF TEMPERTURE		TEMPERTURE -55→15~35→ 85→15~35°C TIME 30→ 2~ 3→ 30→ 2~ 3 min. UNDER 5 CYCLES.			3)NO DAMAGE, CRACK AND LOOSENESS OF PART.			X —					
DRY HEAT		EXPOSED AT 85 °C, 96 h.			1)CONTACT RESISTANCE: 80 mΩ MAX.			X —					
COLD		EXPOSED AT -55 °C, 96 h.			2)NO DAMAGE, CRACK AND LOOSENESS OF PART.			X —					
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.			NO HEAVY CORROSION.			X —					
SULPHUR DIOXIDE		EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD:JIS C 0090)			1)CONTACT RESISTANCE: 80 mΩ MAX. 2)NO HEAVY CORROSION.			X —					
RESISTANCE TO SOLDERING HEAT		REFLOW RECOMMENDED TEMPERATURE PROFILE 25°C (60 S) 150°C 160°C (60~90 S) 240°C 5 S MAX 200°C (20~30 S) TO BE TESTED UNDER THE ABOVE CONDITIONS			NO MELTING OF RESIN WHICH AFFECTS THE PERFORMANCE OF COMPONENT			X —					
SOLDRABILITY		SOLDERED AT SOLDER TEMPERATURE, 235 °C FOR IMMERSION DURATION, 2 s.			NO PINHOLE OR DEWETTING ON SOLDERED SURFACE.			X —					
REMARKS				DRAWN		DESIGNED		CHECKED		APPROVED		RELEASED	
				 00.01.15		 00.01.15		 00.01.17		 00.01.17			
UNLESS OTERWISE SPECIFIED, REFER TO JIS C 5402.													
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST X: APPLICABLE TEST													
HS HIROSE ELECTRIC CO. LTD.				SPECIFICATION SHEET				PART NO. FX11B - 100P - SV0.5					
CODE NO. (OLD)				DRAWING NO.				CODE NO.				1	
CL				ELC4 - 152628 -				CL 573 - 0653 - 5 -				1	