



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Hermaphroditic Connector**

PCB Mount Orientation: **Vertical**

Connector System: **Board-to-Board**

Number of Positions: **10**

Number of Rows: **1**

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Hermaphroditic Connector
Connector System	Board-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Stacking Configuration	Stack Through
Number of Columns	10
Number of Loaded Positions	10
Stackable	Yes
PCB Mount Orientation	Vertical
Number of Positions	10
Number of Rows	1
Board-to-Board Configuration	Parallel

Electrical Characteristics

Dielectric Withstanding Voltage (Max)	500 Vrms
---------------------------------------	----------

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Layout	Inline
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Hermaphroditic
Contact Current Rating (Max)	2.7 A

Termination Features

Termination Method to Printed Circuit Board	Surface Mount
---	---------------

Mechanical Attachment

PCB Mount Alignment Type	Locating Posts
PCB Mount Retention Type	Location Peg
Mating Alignment	With
PCB Mount Retention	Without
PCB Mount Alignment	With
Connector Mounting Type	Board Mount

Housing Features

Mating Entry Location	Top
Centerline (Pitch)	.8 mm[.031 in]
Housing Material	PPA

Dimensions

Connector Length	10.36 mm[.409 in]
Connector Height	4.55 mm[.179 in]
Connector Width	3.9 mm[.153 in]
Stack Height	5 mm[.197 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-50 – 125 °C[-58 – 257 °F]



Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

Compatible With Agency/Standards Products	DIN, UL
Compatible With Approved Standards Products	UL
Industry Standard	IEC
UL Flammability Rating	UL 94V-0

Packaging Features

Packaging Reel Diameter	330 mm[12.99 in]
Packaging Quantity	1300
Packaging Method	Tape & Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Yet Reviewed for halogen content
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts





TE Part # 224920-E  
MICROS STV 9 407 188 \* 0007 J 3  
224920 M



TE Part # 354000-E  
MICROS STV 54 407 188 9999 0007 J 3  
3540

Also in the Series | ERNI MicroStac



PCB Headers & Receptacles(9)

Customers Also Bought



TE Part #8-338069-0  
MICRO-MATCH SMD FTE



TE Part #640456-4  
04P MTA100 HDR ASSY F/L SQ STR



TE Part #2-1393243-1  
RTE25024



TE Part #826470-4  
2X4P MOD II SHROUDED HEADER,  
RT ANG.



TE Part #215460-6  
MICRO-MATCH FEM.SE



TE Part #4391-BHQ-T-005-001  
5 PSI Differential Sensor



TE Part #5391-BHQ-T-001-001  
1 PSI Differential Sensor



TE Part #3-1625867-3  
RP 1J 0.166W 13R3 0.1% 25PPM 1K RL



TE Part #284257-E  
MICROS STV 14 407 188 \* 0007 J 3  
284257



TE Part #9-2176483-3  
RA73F 2A 4K99 0.1% 5K RL



Documents

Product Drawings

MICROS STV 10 407 188 \* 0007 J 3 354863

English

CAD Files

Customer View Model

ENG\_CVM\_CVM\_354863-E\_1.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_354863-E\_1.3d\_stp.zip

English

Customer View Model

ENG\_CVM\_CVM\_354863-E\_1.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.