




STRADA

TE Internal #: 5-2149781-1  
PCB Mount Receptacle, Vertical, Board-to-Board, 161 / 48 Position,  
1.27 mm / 3.04 mm / 6.09 mm [.05 in / .12 in / .24 in] Centerline,  
Gold  
[View on TE.com >](#)

Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: **PCB Mount Receptacle**  
PCB Mount Orientation: **Vertical**  
Connector System: **Board-to-Board**  
Number of Positions: **48, 161**  
Centerline (Pitch): **1.27 mm, 3.04 mm, 6.09 mm [ .05 in, .12 in, .24 in ]**

Features

Product Type Features

PCB Connector Assembly Type	PCB Mount Receptacle
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Pairs per Column	4
Number of Power Positions	0
Number of Pairs	48
Number of Loaded Positions	161
Stackable	No
Number of Signal Positions	4
PCB Mount Orientation	Vertical
Number of Positions	48, 161
Board-to-Board Configuration	Parallel

Electrical Characteristics

Operating Voltage	0 VDC
-------------------	-------

Body Features

Primary Product Color	Natural
-----------------------	---------



Contact Features

PCB Contact Termination Area Plating Material Thickness	.5 – 2.54 μm[19.68 – 100 μin]
Contact Layout	Staggered
Mating Tab Width	.69 mm[.027 in]
Mating Tab Thickness	.41 mm[.015 in]
PCB Contact Termination Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
	3 μin
Contact Type	Socket
Contact Current Rating (Max)	1.5 A, 18 A

Termination Features

Rectangular Termination Post & Tail Thickness	.15 mm[.005 in]
Rectangular Termination Post & Tail Width	.43 mm[.016 in]
Termination Post & Tail Length	1.47 mm[.057 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit

Mechanical Attachment

PCB Mount Alignment Type	Post Polarization
PCB Mount Retention Type	Solder Tail
Mating Alignment	With
Mating Alignment Type	Polarizing Tab
PCB Mount Retention	With
PCB Mount Alignment	With
Connector Mounting Type	Board Mount

Housing Features

Mating Entry Location	Top
Centerline (Pitch)	1.27 mm, 3.04 mm, 6.09 mm[.05 in][.12 in][.24 in]
Housing Material	Matte

Dimensions

Connector Height	7.29 mm[.287 in]
------------------	------------------

Usage Conditions



Operating Temperature Range	-55 – 85 °C[-67 – 185 °F]
-----------------------------	---------------------------

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	32
Packaging Method	Package

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2024 (240) Candidate List Declared Against: JAN 2024 (240) Does not contain REACH SVHC
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 6-2149780-1  
STRADA MESA,HD,HF,048,000,00,SN,  
Y,11

TE Part # 1-2149780-1  
STRADA MESA,HD,HF,048,000,00,PB,  
Y,11

Customers Also Bought

TE Part #5748901-1  
AMP III RCPT 25P RA 318 THD IN

TE Part #1-1939638-0  
DYNAMIC 1100D HDR ASSY H 40P  
XBLACK GOLD

TE Part #1747994-1  
DYNAMIC D-2100 V-HDR ASS'Y 16P X-  
KEY

TE Part #1-1623821-1  
CFH 1100 5R6 5% 300mm Leads

TE Part #31172  
BODY,RING TONGUE 22-18

TE Part #5406275-3  
MJ ASSY,4P,8POS,SH,RVPGT,CAT5

TE Part #1934226-1  
Tin man Recpt Assy3pair8 Colum

TE Part #31173  
BODY,RING TONGUE 22-18

TE Part #9-338069-4  
MICRO-MATCH SMD FTE

TE Part #2-320573-3  
TERMINAL,PIDG R IR 18 3/8

Documents

Product Drawings

STRADA MESA,RC,HF,048,000,00,SN,Y,NA

English

CAD Files

Customer View Model

ENG\_CVM\_CVM\_5-2149781-1\_2.2d\_dxf.zip

English

3D PDF



3D

Customer View Model

[ENG\\_CVM\\_CVM\\_5-2149781-1\\_2.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_5-2149781-1\\_2.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

[Product Specifications](#)

[Application Specification](#)

English