RATING	OPERATING TEMPERATURE RANGE		-25	°C TO	+85	°C	STORAGE RANGE	E TEMPERAT	URE	-10 ∘	СТО	+60	°C	
	VOLTAGE						_							
	CURRENT							ICABLE CABLE		ϕ 10±0.5mm				
				SPE	CIF	ICAT	IONS	S						
IT	EM		TEST	METHO)				REQU	IREMENTS			QT	AT
CONSTR	UCTION													
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.					ACC	ACCORDING TO DRAWING.					Х	Х
MARKING		CONFIRMED VISUALLY.											-	_
		CHARACTERISTICS												
CORROSION SALT MIST								NO HEAVY CORROSIN RUIN THE FUNCTION.					Χ	_
SEALING (1)		EXPOSED	AT A DEPTH OF	1.8 m FC	OR 48	h.	NO	WATER PE	NETRATI	ON INSIDE CO	NNECTOF	₹.	Χ	_
AIRTIGHTNESS (1)		APPLY AT	R PRESSURE 18 OR.	kPa FOR	0. 5m	in TO INS	SIDE NO	AIR BUBBI	_ES INS	IDE CONNECTO	R.		Х	-
COUN	T DE	SCRIPTI	ON OF REVISIO	DNS		D	ESIGNE	ΞD		CHECKE	D		DA	TE
Δ														_
REMARK	•	TNESS SHALL BE TESTED BY APPLICABLE CONNECTOR						APPF	ROVED	HY. KOBA	YASHI		18. 02	2. 26
NOTES (1) SEAL I	NG AND AIRTIGHT							CHECKED DESIGNED		HY. KOBA	YASHI			2. 26
										TH. KAI	MEYA			2. 23
Unless oth	nerwise spe	cified, re	ied, refer to JIS C 5402.(IEC 60512)				DRAWN		AWN	MK. INOUE		18. 02	2. 23	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test D						DRA	RAWING NO. ELC-1104			10458	8–31	-00		
HS	SI	PECIFICATION SHEET				Р	PART NO.			JR13WCC-10 (31)				
	HIR	OSE ELECTRIC CO., LTD.				С	CODE NO.		CL114-2051-3-31				7	1/1