

APPLICABLE STANDARD							
RATING	OPERATING TEMPERATURE RANGE	-25 °C TO +85 °C	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C			
	_____	_____	_____	_____			
	_____	_____	APPLICABLE CABLE	φ 8±0.5 mm			
SPECIFICATIONS							
ITEM		TEST METHOD		REQUIREMENTS		QT AT	
CONSTRUCTION							
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X X	
MARKING		CONFIRMED VISUALLY.				- -	
ENVIRONMENTAL CHARACTERISTICS							
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 500 h.		NO HEAVY CORROSION.		X -	
SEALING <sup>(1)</sup>		EXPOSED AT A DEPTH OF 1.8 m FOR 48h.		NO WATER PENETRATION INSIDE CONNECTOR.		X -	
AIRTIGHTNESS <sup>(1)</sup>		APPLY AIR PRESSURE 18 kPa FOR 30s TO INSIDE CONNECTOR		NO AIR BUBBLES INSIDE CONNECTOR		X -	
COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED	DATE	
0							
REMARK				APPROVED	HY. KOBAYASHI	18.03.15	
NOTE(1) SEALING AND AIRTIGHTNESS SHALL BE TESTED BY APPLICABLE CONNECTOR.				CHECKED	HY. KOBAYASHI	18.03.15	
				DESIGNED	TH. KAMEYA	18.03.15	
Unless otherwise specified, refer to IEC 60512.(JIS C 5402)				DRAWN	TH. KAMEYA	18.03.15	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC-110598-31-00		
	SPECIFICATION SHEET		PART NO.	JR13WCC-8 (31)			
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL114-2049-1-31		1/1	