





- Notes
- 1 The recommended tightening torque of ref.No. ① shall be 2 to 3N · m.  
LOCTITE 263, HENKEL JAPAN or equevalent is recommended to prevent  
ref. No. ① from loosening.
  - 2 Across flats of hexagon hole of ref. No. ⑤ to be 1.27.  
The recommended tightening torque of ref.No. ⑤ shall be 0.3 to 0.4N · m.
  - 3 The cable pull and twisting strength(, waterproof tightness) and  
other characteristics may differ, depending on the cable structure,  
please confirm before the use.

3	Chloroprene rubber	(Black)								
2	Brass	Nickel plating	5	Stainless steel	JIS B 1177 Hexagon socket set screw M2.6×0.45×2					
1	Brass	Nickel plating	4	Brass	Nickel plating JIS B 1111 Pan head machine screw M3×0.5×8					
NO.	MATERIAL	FINISH . REMARKS		NO.	MATERIAL	FINISH . REMARKS				
UNITS mm				SCALE 2 : 1		COUNT 1	DESCRIPTION OF REVISIONS DIS-C-00007459	DESIGNED TY. SUZUKI	CHECKED HY. KOBAYASHI	DATE 20211208
 HIROSE ELECTRIC CO., LTD.				APPROVED : HY. KOBAYASHI		20180222	DRAWING NO. EDC-112372-31-00			
				CHECKED : HY. KOBAYASHI		20180222	PART NO. RM24WTP-CP14(31)			
				DESIGNED : HY. KISHI		20180222	CODE NO. CL0109-1851-9-31			
				DRAWN : MK. INOUE		20180208	 1/1			
FORM HC0011-5-51										