

1		2		3		4		5		6		7		8			
								REV.		ECN NO.		DATE		SIGN		DESCRIPTION	
								B		LEN14B0187		2014/11/10		Ruru		Change Logo LTW To ALTW	
								C		LEN1530064		2015/02/12		Ruru		Change Logo	
								D		C230202		2023/02/16		Vicky		△D X2	

<

1		2		3		4		5		6		7		8	
REV.		ECN NO.		DATE		SIGN		DESCRIPTION							
B		LEN14B0187		2014/11/10		Ruru		Change Logo LTW To ALTW							
C		LEN1530064		2015/02/12		Ruru		Change Logo							
D		C230202		2023/02/16		Vicky		△D X2							

Housing 1

O-Ring 3

21.1 ±0.5

2.0

4 Screw

15.2

7.1

ALTW

Lock Nut 2

Inner Mold 6

Outer Mold 7

5 Rubber Lead

78.0 (Ref.)

10.60

10.00

ALTW

B

Note:

*

⌀

 Important Dimension.

* Waterproof Rate: IP67

* Housing: Nylon+GF, Black

* Lock Nut: Nylon+GF, Black

* O-Ring: EPDM, Black

* Rubber Lead: TPES, Black

* Screw is not allowed to tight (Chain be revolve)

不可將螺絲鎖緊, (鏈條要可旋轉)

* Drill Hold

⌀

 2.3mm, Depth 4mm.

鑽孔

⌀

 2.3mm, 深4mm

UNIT: mm				TITLE		ACC, CERES, WP CAP		2LOCK, W/RB LEAD		△D	
TOLERANCE				SCALE		SIZE		SHEET		OF	
.X ±0.25				2:1		A4		1		1	
.XX ±0.1				REV.		WC-REV.		A.2		⌀: Inspection item	
.XXX ±0.05				D		A.2		⌀: Inspection item			
ANGLES ±1°											

Amphenol LTW

安費諾亮泰企業股份有限公司

ITEM NO		CAP-WAAMLPC2		DRAWN BY		Ruru		DATE		2015-02-12	
DWG NO		CAP-WAAMLPC2		CHECKED BY		Rita		DATE		2015-02-12	
CUSTOMER		ALTW		APPROVED BY		Lion		DATE		2015-02-12	

1

2

3

4

5

6

7

8

W10814-03-BW01A2

1		2		3		4		5		6		7		8	
REV.		ECN NO.		DATE		SIGN		DESCRIPTION							
B		LEN14B0187		2014/11/10		Ruru		Change Logo LTW To ALTW							
C		LEN1530064		2015/02/12		Ruru		Change Logo							
D		C230202		2023/02/16		Vicky		△D X2							

<
