

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-40℃ TO +85℃	STORAGE TEMPERATURE RANGE	-40℃ TO +85℃	
	POWER	100 W	CHARACTERISTIC IMPEDANCE	50Ω (0.8 TO 2.2 GHz)	
	USED CONNECTOR	95% MAX(NO CONDENSATION)	WATERPROOF	IPX7	
	—	—	USED CONNECTOR	N-J	
SPECIFICATIONS					
ITEM		TEST METHOD		REQUIREMENTS	
QT		AT			
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	
MARKING		CONFIRMED VISUALLY.			
ELECTRIC CHARACTERISTICS					
V.S.W.R.		MUST BE UNDER THE STD.VALUE AT FREQUENCY 0.8 TO 2.2 GHz		1.3 MAX	X X
INSERTION LOSS		MUST BE UNDER THE STD.VALUE AT FREQUENCY 0.8 TO 2.2 GHz		0.2 dB MAX	X X
MECHANICAL CHARACTERISTICS					
MECHANICAL OPERATION		100 TIMES INSERTIONS AND EXTRACTIONS		①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X —
VIBRATION		FREQUENCY 10 TO 2000 Hz, TOTAL AMPLITUDE 1.52 mm, 196 m/s ² AT 4 HOURS, FOR 3 DIRECTIONS.		①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X —
SHOCK		ACCELERATION:490m/s ² DURATION:11m/s ² , HALF SINE WAVE 3 BOTH AXIAL DIRECTIONS.		①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X —
ENVIRONMENTAL CHARACTERISTICS					
MOISTURE RESISTANCE		EXPOSE TO -10~+65℃, 80 ~ 100 %, 10 CYCLES (240 HOURS.) THEN LEAVE IT FOR ONE HOUR OR TWO IN THE AMBIENT TEMPERATURE AND HUMIDITY.		①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X —
RAPID CHANGE OF TEMPERATURE		TEMPERATURE-58~-55→20~35→85~88→20~35℃ TIME 30 → 5MAX → 30 → 5MAX min TEST 5 CYCLES AND LEAVE IT FOR ONE HOUR OR TWO.		①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X —
SURGE IMMUNITY TEST		IEC61000-4-5 ED2 LEVEL4 APPLY COMBINATION WAVE(1.2/50 μs,8/20 μs) ±4kV ,5 EACH TIMES		①ELECTRICAL CHARACTERISTIC SHALL BE MET. ②NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X —
IMPULSE WISTANDING		APPLY IMPULSE WHICH HAS THE DURATION IN 8/20 MICRO SECONDS AND THE WAVEFORM OF PLUS/MINUS 50ka AT EACH FIVE TIMES.		NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X —
		APPLY IMPULSE WHICH HAS THE DURATION IN 10/350 MICRO SECONDS AND THE WAVEFORM OF PLUS/MINUS 35ka AT EACH ONE TIME.		NO DAMAGE, CRACK, AND LOOSENESS, OF PARTS.	X —
SALT SPRAY (CORROSION)		EXPOSE TO 5 % SALT WATER SPRAY FOR 48 HOURS.		NO CORROSION WHICH AFFECTS THE OPERATION OF COMPONENT.	X —
WATER PROOF		SUBMERGE IT AT THE DEPTH OF 1 METER FOR 30 MINUTES IN A PROPER CONDITION.		NO WATER INTRUSION INTO CONNECTOR INSEIDE.	X —
AIR PRESSURE WITHSTANDING		APPLY AIR PRESSURE OF 17.6 kPa FOR 30 SECONDS IN A PROPER CONDITION.		NO SEQUENTIAL LEAKAGE OF BUBBLE FROM CONNECTOR INSIDE.	X X
△	COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED
0					
REMARK (1)RoHS COMPLIANT (2)NOT INCLUDE THE ADAPTER LOSS IN INSERTION LOSS. Unless otherwise specified, refer to IEC 60512.				APPROVED	KY. SHIMIZU
				CHECKED	TO. KATAYAMA
				DESIGNED	YI. FUNADA
				DRAWN	YI. FUNADA
Note QT:Qualification Test AT:Assurance Test X:Applicable Test				DRAWING NO. ELC-178986-00-00	
HRS	SPECIFICATION SHEET		PART NO.	CP-N-JJS-1	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL355-0134-0-00	△ 1/1