

APPLICABLE STANDARD						
RATING	OPERATING TEMPERATURE RANGE	-55°C TO +125°C(95%RH MAX)	STORAGE TEMPERATURE RANGE	-55°C TO +125°C(95%RH MAX)		
	POWER	—— W	CHARACTERISTIC IMPEDANCE	5 0 Ω (0.045 TO 65 GHz)		
	PECULIARITY	——	APPLICABLE CABLE	——		
SPECIFICATIONS						
ITEM		TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION						
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
MARKING		CONFIRMED VISUALLY.			—	—
ELECTRIC CHARACTERISTICS						
CONTACT RESISTANCE	100 mA MAX (DC OR 1000 Hz).	CENTER CONTACT	16 mΩ MAX.	X	X	
		OUTER CONTACT	16 mΩ MAX.	X	X	
INSULATION RESISTANCE	250 V DC.	500 MΩ MIN.		X	X	
VOLTAGE PROOF	250 V AC FOR 1 min.CURRENT LEAKAGE 2mA MAX.	NO FLASHOVER OR BREAKDOWN.		X	X	
RETURN LOSS	FREQUENCY 0.045 TO 65 GHz.	RETURN LOSS	15dB MIN : 0.045 TO 40 GHz 10dB MIN : 40 TO 65 GHz	X	X	
INSERTION LOSS	FREQUENCY TO GHz	dB MAX.		—	—	
MECHANICAL CHARACTERISTICS						
CONTACT INSERTION AND EXTRACTION FORCES	BY STEEL GAUGE.	INSERTION FORCE	N MAX.	—	—	
		EXTRACTION FORCE	NMIN	—	—	
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	INSERTION FORCE	N MAX.	—	—	
		EXTRACTION FORCE	N MAX.	—	—	
MECHANICAL OPERATION	100 TIMES INSERTIONS AND EXTRACTIONS.	1) CONTACT RESISTANCE: CENTER CONTACT 28 mΩMAX.CHANGE OUTER CONTACT 28 mΩMAX.CHANGE 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	—	
VIBRATION	FREQUENCY 10 TO 500 Hz SINGLE AMPLITUDE 0.75 mm, 98 m/s ² AT 10 CYCLES FOR 3 DIRECTIONS.	1) NO ELECTRICAL DISCONTINUITY OF 1μs. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	—	
SHOCK	490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.			X	—	
CABLE CLAMP ROBUSTNESS (AGAINST CABLE PULL)	APPLYING A PULL FORCE THE CABLE AXIALLY AT N MAX.	1) NO WITHDRAWAL AND BREAKAGE OF CABLE. 2) NO BREAKAGE OF CLAMP.		—	—	
ENVIRONMENTAL CHARACTERISTICS						
DAMP HEAT,CYCLIC	EXPOSED AT -10 TO +65 °C, 90~98 % TOTAL 10 CYCLES (240 h)	1) INSULATION RESISTANCE: 100 MΩ MIN. (AT HIGH HUMIDITY) 2) INSULATION RESISTANCE: 500 MΩ MIN. (AT DRY) 3) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	—	
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -65 → — → +125 → — °C TIME 30 → 3 → 30 → 3 min. UNDER 5 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X	—	
CORROSION SALT MIST	EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.	NO HEAVY CORROSION		X	—	
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE		
0						
REMARK RoHS COMPLIANT			APPROVED	MH. YAMANE	08.07.19	
			CHECKED	TS. NOBE	08.07.18	
			DESIGNED	RO. YOKOYAMA	08.07.14	
			DRAWN	RO. YOKOYAMA	08.07.14	
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.	ELC4-313091-00		
HRS	SPECIFICATION SHEET		PART NO.	SMPMP (FD) -HVP		
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL311-0419-5-00	△ 1/1	