Rating Power	App	licable standa	rd			•							
Rating Power	Operating			-40 °C to ±105 °C(90 %RF	Max)	Storag	ge			-40 °C to +90 °C(90 %R		x)	
Rating Power W		temperature r	ange	10 0 10 1103 0()0 /0141		•							
Peculiarity	Rating	Power		W				С		75 O(0 to 12 GHz)			
Peculiarity	Tuuring										-/		
SPECIFICATIONS		Peculiarity					cable			1.5 Dia. coaxial cable(Greet			
TIEM													
General examination Visually and by measuring instrument. According to drawing. X X LECTRICAL CHARACTERISTICS S00 MQ Min. X X Insulation resistance 100 V DC. S00 MQ Min. X X Withstanding to yak Cord Time, current leakage 2 mA Max. No flashover or breakdown. X X Woltage standing Frequency 0.0 3 GHz. VSWR 1.3 Max. (17.04B Min.) X - MECHANICAL CHARACTERISTICS Cable clamp strength (Against cable pull) Of 10 mm/min. and record the strength at which the cable or connector breaks. 14.7 N Min. X - MECHANICAL CHARACTERISTICS Cable clamp strength (Against cable pull) Of 10 mm/min. and record the strength at which the cable or connector breaks. 14.7 N Min. X - MECHANICAL CHARACTERISTICS Cable clamp strength Against cable pull) Of 10 mm/min. and record the strength at which the cable or connector breaks. 14.7 N Min. X - MECHANICAL CHARACTERISTICS Cable clamp strength Against cable pull) Of 10 mm/min. and record the strength at which the cable or connector breaks. 14.7 N Min. X - MECHANICAL CHARACTERISTICS Against cable pull) Of 10 mm/min. and record the strength at which the cable or connector breaks. 14.7 N Min. X - MECHANICAL CHARACTERISTICS Against cable pull) Of 10 mm/min. and record the strength at which the cable or connector breaks. 14.7 N Min. X - MECHANICAL CHARACTERISTICS Against cable pull) Of 10 mm/min. and record the strength at which the cable or connector breaks. 14.7 N Min. Office of 1.2 N Min. Office of					FICA	LIONS	<u> </u>						
Ceneral examination Visually and by measuring instrument. According to drawing. X X				TEST METHOD				R	EQUI	REMENTS	QT	AT	
ELECTRICAL CHARACTERISTICS			ı										
Installation resistance Withstanding voltage 200 V AC for 1 min. current leakage 2 mA Max. No flashover or breakdown. Voltage standing Prequency 0 to 3 GHz VSWR 1.3 Max. (17.7dB Min.) Prequency 3 to 12 GHz. VSWR 1.5 Max. (13.9dB Min.) Prequency 3 to 12 GHz. VSWR 1.5 Max. (13.9dB Min.) Prequency 3 to 12 GHz. VSWR 1.5 Max. (13.9dB Min.) Prequency 3 to 12 GHz. VSWR 1.5 Max. (13.9dB Min.) Prequency 3 to 12 GHz. VSWR 1.5 Max. (13.9dB Min.) Prequency 3 to 12 GHz. VSWR 1.5 Max. (13.9dB						A	Accordi	ng to c	lrawing	<u>.</u>	X	X	
Withstanding voltage Voltage standing Voltage standing Voltage standing Voltage standing Voltage standing Frequency 0 to 3 GHz. VSWR 1.3 Max. (17.7dB Min.) VSWR 1.3 Max. (17.7dB Min.) VSWR 1.5 Max. (13.9dB Min.) VSWR 1.5 Max. (13.9dB Min.) VSWR 1.6 Max.													
Frequency 0 to 3 GHz VSWR 1.3 Max. (17.7dB Min.) X -													
wave ratio (Return Loss) Frequency 3 to 12 GHz. VSWR 1.5 Max. (13.9dB Min.) X — MECHANICAL CHARACTERISTICS Cable clamp strength (Against cable pull) Using a pulling tester, pull the cable axially at a rate of 10 mm/min. and record the strength at which the cable or connector breaks. 14.7 N Min. X — Count Description of revisions Designed Checked Date— Remark NOTE VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No. 0 DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No. 0 DFL75-2LPP-084N9D-A-L		0 0									X	X	
Count Description of revisions Designed Checked Date		nding 1	Frequency 0 to 3 GHz.				VSWR	1.3	Max. (17.7dB Min.)	v	_	
MECHANICAL CHARACTERISTICS Cable clamp strength (Against cable pull) of 10 mm/min. and record the strength at which the cable or connector breaks. Late			Frequency 3 to 12 GHz.			v	VSWR	1.5	1.5 Max. (13.9dB Min.)				
Cable clamp strength (Against cable pull) Count Description of revisions Designed Checked Date	`		Freque	Frequency - to - GHz.			dB	Max.			_	_	
Cable clamp strength (Against cable pull) Count Description of revisions Designed Checked Date	MECHA	ANICAL CE	IARA	CTERISTICS									
Count Description of revisions Designed Checked Date								Min.					
Count Description of revisions Designed Checked Date	(Against ca	ıble pull)									X	_	
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.			the cab	le or connector breaks.									
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.													
Remark NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.	Cou	nt	Descr	scription of revisions		Desig	signed			Checked I		ate	
NOTE 1 VSWR was measured with BNC(75)J-D.FL75J-BPA conversion adapters. 2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. BYK.KIUCHI 20200131 Drawn YK.KIUCHI 20200131 Drawn YK.KIUCHI 20200131 Drawn DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.	N												
2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Orawing No. SPECIFICATION SHEET Part No. HIROSE ELECTRIC CO., LTD. Checked NK.NINOMITA 20200131 Designed YK.KIUCHI 20200131 Drawn YK.KIUCHI 20200131 Drawn DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. O 1/1	Remark							App	roved	NK.NINOMIYA	2020	00131	
2. Specifications are subject to change without notice. HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Orawing No. SPECIFICATION SHEET Part No. HIROSE ELECTRIC CO., LTD. Checked NK.NINOMITA 20200131 Designed YK.KIUCHI 20200131 Drawn YK.KIUCHI 20200131 Drawn DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. O 1/1	NOTE 1 VSWR was measured with RNC(75)LD FL75LRPA conversion adapters								NIZ NINOMINA	2020	00121		
HALOGEN FREE Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.	Checked NK.NINOMITA								NK.NINOMI YA	2020)0131		
Unless otherwise specified, refer to IEC 60512. Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.	2	-		ibject to change without notice.				Designed		YK.KIUCHI	20200131		
Note QT:Qualification Test AT:Assurance Test X:Applicable Test Drawing No. SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.	I Imlant 14			on to IEC 60510			}	Drawn		AK KIIIGHI	20200131		
SPECIFICATION SHEET Part No. DFL75-2LPP-084N9D-A-L HIROSE ELECTRIC CO., LTD. Code No.	Uniess of	ierwise specifi	ieu, refe	EI 10 IEC 00312.				טני	ıwıı	1 K.KIUCIII	2020	,0131	
HIROSE ELECTRIC CO., LTD. Code No. 0 1/1	Note QT:0	Qualification Test	AT:Ass	urance Test X:Applicable Test	Dra								
HIROSE ELECTRIC CO., LTD. Code No.	l ma	SF	ECIF	ICATION SHEET	Part No.			DFL75-2LPP-084N9D		A-L			
		HIRC	SE E	ELECTRIC CO., LTD.		Code No.					0	1/1	