


	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE		COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△						△					
△						△					
APPLICABLE STANDARD											
RATING	OPERATING TEMPERATURE RANGE		-55 °C TO 85 °C			STORAGE TEMPERATURE RANGE		°C TO °C			
	VOLTAGE		250 V AC			OPERATING HUMIDITY RANGE		% TO %			
	CURRENT		0.5 A			APPLICABLE CABLE					
SPECIFICATIONS											
ITEM		TEST METHOD				REQUIREMENTS			QT	AT	
CONSTRUCTION											
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.			○	○	
MARKING		CONFIRMED VISUALLY.							○	○	
ELECTRIC CHARACTERISTICS											
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz). 1				35 mΩ MAX.			○	○	
INSULATION RESISTANCE		500 V DC.				500 MΩ MIN.			○	○	
VOLTAGE PROOF		500 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.			○	○	
MECHANICAL CHARACTERISTICS											
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR.				10.2 N MIN. 38.2 N MAX.			○	—	
MECHANICAL OPERATION		1000 TIMES INSERTIONS AND EXTRACTIONS. 1				① CONTACT RESISTANCE: 35 mΩ MAX. ② NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			○	—	
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, — m/s ² AT 2 h, FOR 3 DIRECTIONS.				NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			○	—	
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 6 DIRECTIONS.							○	—	
ENVIRONMENTAL CHARACTERISTICS											
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → 5~35 → 85 → 5~35 °C TIME 30 → 2~3 → 30 → 2~3 min UNDER 5 CYCLES.				NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			○	—	
DAMP HEAT (STEADY STATE)		EXPOSED AT 40 °C, 90~95 %, 96 h.				INSULATION RESISTANCE: 1 MΩ MIN. (AT HIGH HUMIDITY.) 100 MΩ MIN. (AT DRY.)			○	—	
CORROSION SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h.				NO HEAVY CORROSION.			○	—	
RESISTANCE TO SOLDERING HEAT		SOLDER TEMPERATURE, 260 ± 5 °C FOR IMMERSION, DURATION 10 ± 1 S.				NO DEFORMATION OF CASE AND EXCESSIVE LOOSENESS OF THE TERMINALS.			○	—	
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, 245 ± 2 °C FOR IMMERSION, DURATION 3 ± 1 S.				MIN. 95 % OF SOLDER IMMersed AREA SHALL BE COVERED NEW SOLDER COATING.			○	—	
NOTE. 1 MEASUREMENT POINT OF CONTACT RESISTANCE											
											
REMARKS						DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
Unless otherwise specified, refer to JIS C 5402.						2-11-16	2-11-16	Y. Enami	H. M. Wada		
Note QT:Qualification Test AT:Assurance Test ○:Applicable Test						03.10.16	03.10.16	03.10.16	03.10.16		
HS HIROSE ELECTRIC CO., LTD.						SPECIFICATION SHEET			PART NO.		
CODE NO.(OLD)						DRAWING NO.			CODE NO.		
CL						ELC4-041444-01			DX20M-26S(50) CL230-5014-0-50		
									1/1		