APPLICA	BLE STAN	DARD									
	OPERATING TEMPERATUR	E RANGE	−25°C TO +85°C	l I	STORAGE FEMPERATURE	RANGE		−25°C TO +60°C			
RATING	RATING VOLTAGE CURRENT				APPLICABL						
			SPECIF	FICAT	IONS						
	EM		TEST METHOD			REQUIREMENTS			QT	АТ	
	XAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.			ACCO	ACCORDING TO DRAWING.			Х	Х	
									- / ·	\ \ \	
COUN	T DE	SCRIPTI	ON OF REVISIONS		ESIGNED	SIGNED		CHECKED		DATE	
1			DIS-E-00011415		M JAEHYEON			KG. OKITA	202210		
REMARK						APPRO'	VED	AO. SUZUKI	2009	90507	
						CHECK		KN. ICHIKAWA		90507	
						DESIGN		MO. SHIMOYAMA	_	90507	
			refer to JIS C 5402.		DRAW		/N			90507	
Note QT:Qualification Test AT:Assurance Test X:Applicable Tes					DRAWING NO.			ELC4-126674-00			
HS.	SF	PECIFI	CATION SHEET		PART NO.	DH-27-CMB (6. 9)					
HIF		ROSE ELECTRIC CO., LTD.			ODE NO.	CL	CL0244-0036-9-00				