

May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	OPERATING&STORAGE HUMIDTY RANGE	85 % MAX	APPLICABLE CABLE	CABLE DIAMETER : $\phi 8.8\pm 0.5$	
SPECIFICATIONS					
ITEM	TEST METHOD		REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.	X	X
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
					
REMARK Unless otherwise specified, refer to JIS C 5402.			APPROVED	AO. SUZUKI	09. 10. 05
			CHECKED	KN. ICHIKAWA	09. 10. 02
			DESIGNED	TU. TANIGUCHI	09. 10. 02
			DRAWN	TU. TANIGUCHI	09. 10. 02
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-126659-00
	SPECIFICATION SHEET		PART NO.	DH-37-CMB (8. 8)	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0033-0-00	 1/