APPLICA	BLE STAN	DARD									
OPERATING TEMPERATURE		-25°C TO ±95°C			STORAGE TEMPERATURE RANGE			−25°C TO +60°C			
RATING	VOLTA	\GE			APPLICAE	BLE CABLE	Λ	Λ CABLE DIAMETER : φ		7.1	
	CURR	ENT						-			
					•		•				
SPECIFICATIONS											
	EM	TEST METHOD			REQUIREMENTS			REMENTS	QT AT		
CONSTRUCTION		I		1	TAGOODDING TO DDAWING			X			
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.  CONFIRMED VISUALLY.				ACCORDING TO DRAWING.				X	
MARKING	MARKING		MED VISUALLY.					X	Х		
COUN	T DE	SCRIPTION OF REVISIONS		 DESIGNED				CHECKED	DA	TE.	
<b>A</b> 2			DIS-E-00003216		KN. ICHIKAWA		TU. TANIGUCHI			20201019	
REMARK	REMARK						VED	AO. SUZUKI	20090511		
THIS PRODUCT SHALL BE MATED WITH DH30B-17S, TO DH30B-17S ABOUT A MECHANICAL, ENVIRONMEN							ŒD	KN. ICHIKAWA	2009	20090511	
	CTERISTICS					DESIGNE		MO. SHIMOYAMA	20090511		
Unless otherwise specified, refer to IEC 60512. 🛕					DRAW			MO. SHIMOYAMA	MA 20090511		
			surance Test X:Applicable T	est	DRAWING N		ELC4-126946-00				
ЖS	SI	SPECIFICATION SHEET			PART NO.		DH-17-CT2B				
11.7	HIR	HIROSE ELECTRIC CO., LTD.			CODE NO.	CL	CL244-0047-5-00 🛕 1/				