APPLICA	BLE STAN	DARD										
7	OPERATING TEMPERATUR		−25°C TO +85°C		STORAGE TEMPERATURE RANGE				−25°C TO +60°C			
RATING	VOLTAGE					PLICABLE CABLE			CABLE DIAMETER :	φ6.4	~7.8	
	CURR	ENT										
	•				•							
			SPEC	IFIC/	IOITA	NS						
	EM		TEST METHOD			REQUIREMENTS				QT	АТ	
CONSTRUCTION GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				X	X	
MARKING		CONFIRMED VISUALLY.				_				X	_ ^	
COUN	T DE	SCRIPTION	ON OF REVISIONS		DESIG	NED			CHECKED	DA	TE	
A 1			E-00014810		KIM JAE				KG. OKITA	2023		
REMARK			MATER WITH BURGE OF IT ARRIVE			APPROV		VED	AO. SUZUKI	2009	0511	
			E MATED WITH DH30B-27S, IT APPLIES MECHANICAL, ENVIRONMENTAL			>	CHECKE		KN. ICHIKAWA	2009	0511	
	ACTERISTIC					DESIGNE		NED	MO. SHIMOYAMA	2009	0511	
Unless oth	erwise spe	cified, re	fer to IEC 60512.	o IEC 60512.			DRAWN		MO. SHIMOYAMA	MOYAMA 20090511		
Note QT:Q	e QT:Qualification Test AT:Assurance Test X:Applicable Test					DRAWING NO.			ELC4-126947-00			
wc	SI	SPECIFICATION SHEET				PART NO.		DH-27-CT2B				
HS.		HIROSE ELECTRIC CO., LTD.			CODE NO.		CI	CL0244-0048-8-00				