APPLICA	BLE STAN	DARD										
	OPERATING TEMPERATURE RANGE		_25°C TO +05°C			STORAGE TEMPERATURE RANGE			−25°C TO +60°C			
RATING	OPERATING&STORAGE HUMIDTY RANGE		85%MAX		APPLICABLE		E CABL	E	A CABLE DIAMETER	~9.3		
	VOLTAGE											
	CURF	RENT										
		<u> </u>	SPECI	IFIC <i>F</i>	ATIO	NS				10-	T	
CONSTRUCTION			TEST METHOD			REQUIREMENTS				QT	AT	
	XAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				Х	Х	
MARKING		CONFIRMED VISUALLY.								Х	Х	
COUN			N OF REVISIONS		DESIGNED				CHECKED	DA	TE	
1 REMARK		DIS-E-00003216			KN. ICH	IKAWA	ADDO	) / E D	TU. TANIGUCHI		1019	
THI			L BE MATED WITH DH40-37S				APPRO		KN. ICHIKAWA		)1117	
OR DH3 * B-37S, IT AP DH3 * B-37S ABOUT A ENVIRONMENTAL CH							DESIGNED		KN. ICHIKAWA	20091117		
									MO. SHIMOYAMA	20091117		
Unless otherwise specified,			refer to IEC 60512.				DRAWN		TM. 0N0 200		1116	
Note QT:Q	ualification Te	st AT:Assu	urance Test X:Applicable T	est	DF	RAWIN	g no. EL		ELC-126588-	C-126588-00-00		
<b>HS</b>	SI	PECIFIC	ATION SHEET		PART NO.			DH-37-CV1B				
HIR		OSE ELI	ECTRIC CO., LTD.		CODE NO.		CL244-0011-8-00		$\triangle$	1/1		