May.1.2024 Copyright 2024 HIROSE ELECTRIC CO., LTD. All Rights Reserved.
In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	−25°C TO +85°C	STORAGE TEMPERATURE RANGE	−25°C TO +60°C
	VOLTAGE		APPLICABLE CABLE	1 CABLE DIAMETER : φ8.5～10.1
	CURRENT			

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION				
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
1	2	DIS-E-00003216	KN. ICHIKAWA	TU. TANIGUCHI	20201019

REMARK
THIS PRODUCT SHALL BE MATED WITH DH30B-51S, IT APPLIES TO DH30B-51S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS.

Unless otherwise specified, refer to IEC 60512. 1

APPROVED	AO. SUZUKI	20090511
CHECKED	KN. ICHIKAWA	20090511
DESIGNED	MO. SHIMOYAMA	20090511
DRAWN	MO. SHIMOYAMA	20090511

Note QT:Qualification Test AT:Assurance Test X:Applicable Test

DRAWING NO. ELC4-126949-00

HRS	SPECIFICATION SHEET	PART NO.	DH-51-CT2B	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL244-0050-0-00 1	1/1

FORM HD0011-2-1