APPLICA	BLE STAN	DARD									
	OPERATING TEMPERATURE RANGE OPERATING&STORAGE HUMIDTY RANGE		-25°C TO +85°C 85%MAX			STORAGE TEMPERATURE RANGE		−25°C TO +60°C			
DATING					APPLICABLE		E CABL	E 🐧	\triangle CABLE DIAMETER : ϕ		10.1
RATING	VOLTAGE										
	CURR	ENT									
		1	SPEC	IFIC <i>P</i>	ATIO	NS					ı
CONSTRUCTION			TEST METHOD			REQUIREMENTS				QT	AT
		VISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.				Х	Х
MARKING		CONFIRMED VISUALLY.								Х	Х
COUN			ON OF REVISIONS		DESIG	SNED			CHECKED	DA	TE
1 DIS-			E-00003216 KN. IO			IKAWA	ADDO	\\/	TU. TANIGUCHI		1019
THI			L BE MATED WITH DH40-51S			APPROV			KN. ICHIKAWA	20091117	
OR DH3 * B-51S, IT AF DH3 * B-51S ABOUT A ENVIRONMENTAL CH							DESIGNED		KN. ICHIKAWA	20091117	
									MO. SHIMOYAMA	20091117	
		-	, refer to IEC 60512.			DRAWN		/VN			
Note QT:Q	ualification Tes	st AT:Ass	surance Test X:Applicable T	est	DF	RAWIN	IG NO.		ELC-126589-00-00		
HS SPECIFI			ATION SHEET		PART NO.			DH-51-CV1B			
	HIR	OSE EL	ECTRIC CO., LTD.		CODE NO.		C	CL244-0012-0-00			1/1