

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25℃ TO +85℃	STORAGE TEMPERATURE RANGE	-25℃ TO +60℃	
SPECIFICATIONS					
ITEM		TEST METHOD	REQUIREMENTS	QT	AT
CONSTRUCTION					
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MECHANICAL CHARACTERISTICS					
VIBRATION		FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES. [1]	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
SHOCK		490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. [1]		X	—
ENVIRONMENTAL CHARACTERISTICS					
THERMAL SHOCK		TEMP -55 →+5 TO +35 →+85 →+5 TO +35 ℃ TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.	NO DAMAGE, CRACK AND LOOSENESS OF PARTS.	X	—
CORROSION SALT MIST		EXPOSED AT 5 % SALT WATER, FOR 48 h.	NO HEAVY CORROSION THAT LOSE FUNCTION.	X	—
COUNT	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
A					
REMARK [1] EXAMINATION IS HELD WITH “DH60-* *P”. Unless otherwise specified, refer to JIS C 5402 .			APPROVED	A0. SUZUKI	09. 04. 27
			CHECKED	M0. SHIMOYAMA	09. 04. 24
			DESIGNED	TS. ITO	09. 04. 24
			DRAWN	TS. ITO	09. 04. 24
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	
HRS	SPECIFICATION SHEET		PART NO.	DH-LNA-W16	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0005-5-00	A /1/1