

APPLICABLE STANDARD						
RATING	OPERATING TEMPERATURE RANGE		-25°C TO +85°C	STORAGE TEMPERATURE RANGE		-25°C TO +60°C
SPECIFICATIONS						
ITEM		TEST METHOD		REQUIREMENTS		QT AT
CONSTRUCTION						
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.		ACCORDING TO DRAWING.		X X
MECHANICAL CHARACTERISTICS						
VIBRATION		FREQUENCY 10 TO 55 Hz SINGLE AMPLITUDE 0.75 mm, 5 min/CYCLE, TOTAL 10 CYCLES. [1]		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X -
SHOCK		490 m/s ² DIRECTIONS OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS. [1]				X -
ENVIRONMENTAL CHARACTERISTICS						
THERMAL SHOCK		TEMP -55 →+5 TO +35 →+85 →+5 TO +35 °C TIME 30 → 5 → 30 → 5 min. UNDER 5 CYCLES.		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		X -
CORROSION SALT MIST		EXPOSED AT 5 % SALT WATER, FOR 48 h.		NO HEAVY CORROSION THAT LOSE FUNCTION.		X -
COUNT	DESCRIPTION OF REVISIONS		DESIGNED		CHECKED	DATE
[A] 0						
REMARK				APPROVED	A0. SUZUKI	09. 04. 27
[1] EXAMINATION IS HELD WITH “DH60- * * P” .				CHECKED	MO. SHIMOYAMA	09. 04. 24
Unless otherwise specified, refer to JIS C 5402 .				DESIGNED	TS. ITO	09. 04. 24
				DRAWN	TS. ITO	09. 04. 24
Note	QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWING NO.		ELC4-126895-00
HRS	SPECIFICATION SHEET			PART NO.	DH-LNA	
HIROSE ELECTRIC CO., LTD.			CODE NO.	CL244-0045-0-00		[A] 1/1