APPLICA	BLE STANI	DARD											
	OPERATING TEMPERATURE R		-55 °C TO 85 °C (1) TEM		TEM	RAGE PERATURE RANGE			-10 °C TO +60 °			(2)	
RATING	VOLTAGE		200 V AC			OPERATING RANGE		TY	40 %	ТО	80 %.		
CURRENT		2 A AP				PLICABLE CABLE AWG#26~36							
			SPEC	IFICA	NOITA	S							
ITEM			TEST METHOD			REQUIREMENTS (ТΩ	ΑТ
CONSTRI						1 1 2 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1							,
			ISUALLY AND BY MEASURING INSTRUMENT.				ACCORDING TO DRAWING.						×
MARKING	70 (1011)	CONFIRMED VISUALLY.					(5),(0				F	×	×
	CHARACT	TERISTICS											-
INSULATION		500 V DC					1000 MΩ MIN.						
RESISTANCE							1000 M 25 MILA					×	
VOLTAGE PROOF		650 V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.						×	_
ENVIRONMENTAL CHARACTERISTICS											•		
DAMP HEAT		EXPOSE	6 h.	①INSULATION RESISTANCE:1000 MΩ MIN						×	_		
(STEADY STATE)		EXPOSED AT 40±2 °C, 90 ~ 95 %, 96 h.				③NO DAMAGE, CRACK AND LOOSENESS OF PARTS.							
RAPID CHANGE OF		TEMPERATURE-55→+5~+35→+85→+5~+35°C					NO DAMAGE, CRACK AND LOOSENESS					×	_
TEMPERATURE		TIME $30 \rightarrow 10 \sim 15 \rightarrow 30 \rightarrow 10 \sim 15$ min.					RTS.						
		UNDER 5 CYCLES.											
COUN	T DE	ESCRIPTI	ON OF REVISIONS		DESIG	NED			CHECKED			DATE	
<u> </u>													
REMARK (1) TEMPERATURE RISE INCLUDED WHEN ENERGIZED						APPF		PPROVED HS. OKAWA		AWA		10, 06	3. 04
'			ATES A LONG-TERM STORAGE STATE CODUCT BEFORE THE BOARD MOUNTED.			CHECKE		KED	HT. YAMA	HT. YAMAGUCHI		10.06	6. 04
TON THE GROOLD PRODUCT BELONE THE BOARD MOUNTED.						DESIGNED		KN. SHII	BUYA	YA 10.06		6. 04	
Unless otherwise specified, refer to MIL-STD-1344.						DRAWN			KY, SUGII				
					DF	RAWING NO.			ELC4-021396-00				
нs	SI	SPECIFICATION SHEET				NO.		A3B-12D-2C					
17	HIR	HIROSE ELECTRIC CO., LTD.			CODE NO		CL621-0309-9-00				<u>/c</u>	7	1/1