APPLIC	ABLE STANI	JAKU						
	OPERATING TEMPERATURE RANGE		-55 °C TO 85 °C ⁽¹⁾	STOR TEMP	AGE PERATURE RANGE	-10 °C TO +60 °	°C (2)	
RATING	OPERATING HUMIDITY RANGE VOLTAGE CURRENT		40 % TO 80 %	STOF HUMI	AGE DITY RANGE	40 % TO 70 %	(2)	
			200 V AC	APF	LICABLE CABLE	AWG #26 TO #36		
			2 A		INSULATION	_		
			SPECIFIC/	ATIONS				
ITEM		TEST METHOD			REQUIREMENTS		QT	ΑT
CONSTRUCT	ION							
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING.			×
MARKING		CONFIRMED VISUALLY.						×
ELECTRIC (CHARACTERIS	TICS						
INSULATION RESISTANCE		500 V DC			1000 MΩ MIN.			_
VOLTAGE PROOF		650 V AC FOR 1 min.			NO FLASHOVER OR	×	_	
ENVIRONME	NTAL CHARAC	TERISTI	ICS					
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.		1) INSULATION RESISTANCE: 1000 MΩ MIN. 2) NO DAMAGE, CRACK AND LOOSENESS OF PARTS.			_	
RAPID CHANGE OF TEMPERATURE		TIME 30 UNDER	TURE → +15 TO +35 → +85 → +15 TO + → 10 TO 15 → 30 → 10 TO CYCLES.		NO DAMAGE, CRACK AND LOOSENESS OF PARTS.		×	_

	COUNT	DESCRIPTION OF REVISIONS	DESIGNED		CHECKED		DATE
$\sqrt{0}$							
REM	IARK			APPROVED		HS. OKAWA	15. 06. 08
	, ,	MPERATURE RISE INCLUDED WHEN ENERGIZED.	AT. IT.	CHECK	KED	HT. YAMAGUCHI	15. 06. 08
	, ,	IS STORAGE INDICATES A LONG-TERM STORAGE : R THE UNUSED PRODUCT BEFORE THE BOARD MOU		DESIGNED		MT. ITANO	15. 06. 08
Unl		r the unused product before the board moon erwise specified, refer to MIL-STD-1344.	NIED.	DRAWN		MT. ITANO	15. 06. 08
Note QT:Qualification Test AT:Assurance Test X:Applicable Test			DRAWIN	DRAWING NO.		ELC-021407-00-00	
Н	RS	SPECIFICATION SHEET	PART NO.	A4B-8S-2C			
-		HIROSE ELECTRIC CO., LTD.	CODE NO.	CL622-0306-7-00			1/1