



TOLERANCE UNLESS OTHERWISE SPECIFIED	
X.	±0.20
.X	±0.15
.XX	±0.10

THIS IS A C.A.D. GENERATED DRAWING  
DO NOT MAKE MANUAL REVISIONS TO MASTER.



ISSUE NUMBER	
ORIGINAL	①
ADD NOTE 4 & 5	
P.M.	AUG. 13/2023 ②



**SPECIFICATION:**

- 1- MATERIAL:  
CONTACT: BRASS GOLD FLASH PLATING ALL OVER NICKEL UNDERPLATING  
HOUSING : PA9T  
MAGNET : N52
- 2- ELECTRICAL :  
RATED VOLTAGE (PER CONTACT): 5V  
RATED CURRENT (PER CONTACT): 2A
- 3- WORKING TEMPERATURE RANGE: -30~+85°C

4- RECOMMENDED SOLDERING PROCESS ARE SELECTIVE SOLDERING OR MANUAL SOLDERING. OTHER FORMS OF SOLDERING SUCH AS WAVE SOLDER OR REFLOW SOLDER ARE NOT RECOMMENDED AND CAN POTENTIALLY CAUSE DEMAGNETIZATION OF MAGNET IN THE CONNECTOR

5- MATING WITH: 685N05222011G1E

**MAGNETIC SPRING LOADED CONNECTOR,  
4POS, FEMALE**

ACAD REFERENCE NO.:	686N05222001G1E	UNIT: MM
DRAWN:	J.L.	DATE: 8/13/2023
CHECKED:	R.S.M	DATE: 8/13/2023
SCALE:	(IN CAD 1:1)	SHEET 1 OF 1
DRAWING NUMBER:	686N05222001G1E	ISSUE 2
PART NUMBER:	686N05222001G1E	



THIS SERIES FULLY CONFORMS TO  
THE EUROPEAN UNION DIRECTIVES  
2011/65/EU FOR RoHS COMPLIANCY.



YOUR CONNECTION TO QUALITY & SERVICE

EDAC INC  
TORONTO, ONTARIO  
CANADA

THESE DRAWINGS AND SPECIFICATIONS  
ARE THE PROPERTY OF EDAC INC., AND  
SHALL NOT BE REPRODUCED, OR COPIED  
OR USED AS THE BASIS FOR THE  
MANUFACTURE OR SALE OF APPARATUS  
WITHOUT WRITTEN PERMISSION.