





## PRODUCT NUMBER

51732-092LF

## NOTES:

I. DIMENSIONS AND TOLERANCES ARE IN ACCORDANCE WITH ASME YI4.5M, 1994 UNLESS OTHERWISE SPECIFIED.

## CONNECTOR NOTES:

- 2. HOUSING MATERIAL: UL 94 V-0 GLASS FILLED HIGH-TEMP THERMOPLASTIC
  POWER CONTACT MATERIAL: COPPER ALLOY
  SIGNAL PIN MATERIAL: COPPER ALLOY
- 3. SEE FCI PLATING SPEC 10064183.
- 4. MANUFACTURER'S NAME, DATE CODE AND OPTIONAL P/N TO APPEAR ON THIS SURFACE. THE MARK CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.
- 5. PRODUCT SPECIFICATION GS-12-149.
  APPLICATION SPECIFICATION BUS-20-067.
- 6. PACKAGED IN TRAYS.

## PCB NOTES:

- 7. ALL HOLE DIAMETERS ARE FINISHED HOLE SIZE.
- (8.) MOUNTING HOLES, WHERE APPLICABLE, ARE UNPLATED.
- 9. Ø1.151±0.025 DRILLED HOLES PLATED WITH
  0.008 MIN SnPb OR Sn OVER 0.03
  TO 0.08 Cu PLATING TO ACHIEVE
  Ø1.02±0.07 HOLE.
- (10.) CONNECTOR KEEP-OUT ZONE.
- (II.) DATUM AND BASIC DIMENIONS ARE ESTABLISHED BY CUSTOMER.

dr	Ruan MT		2015/12/17	proj	projection		1	size A 4	scale	
eng	Ruan MT		2016/01/07				MM		1:1	
chr	Fancy Zhang		2016/01/06				-		-	
appr	Pei-Ming Zheng		2016/01/07	product	family		PwrBlade	rel level	Released	
F	Cj	-	+ 16S HT ANGLE	OTD HEADE	D		ou ōwp	51732-0	092	re v
-	.fci.com			SID HEADE	1	oduct -	° Customer	Drw	sheet 4 of	

[S]

С

opyright FC

D

Pro/E File · REV C · 2009-06-09

PDS: Rev :A

STATUS:Released

Printed: Jan 11, 2016