

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Product image



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

WFS 4
<u>2561900000</u>
W-Series, Fuse terminal, Rated cross-section: 4 mm², Screw connection
4050118570403
50 pc(s).



Open sides

Technical data

Weidmüller Interface GmbH & Co. KG

Snap-on

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and weights			
Width	6.1 mm	Width (inches)	0.24 inch
Height	62.5 mm	Height (inches)	2.461 inch
Depth	75 mm	Depth (inches)	2.953 inch
Depth including DIN rail	75.5 mm	Net weight	17.435 g
Temperatures			
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C
Material data			
Material	Wemid	Colour code	black
UL 94 flammability rating	V-0	23,23. 0000	o.ook
System specifications			
Version	Screw connection, Fuse isolator	Tightening torque (clamping screw for copper conductors)	0.50.6 Nm
End cover plate required	Yes	Number of potentials	1
Number of levels	1	No. of clamping points per level	2
Number of potentials per tier	1	Levels cross-connected internally	No
PE connection	No	Rail	TS 35
N-function	No	PE function	No
PEN function	No		
2 clampable conductors (H0	5V/H07V) with equal c	ross-section (rated connection)	
Wire connection cross section, finely stranded, two clampable wires, min.	0.5 mm²	Wire cross-section, finely stranded, two clampable wires, max.	1.5 mm²
Wire connection cross section, finely stranded with wire-end ferrules DIN		Wire connection cross section, finely stranded with wire-end ferrules DIN	
46228/1, 2 clampable wires, min.	0.5 mm ²	46228/1, 2 clampable wires, max.	1.5 mm ²

Type of mounting

right



Technical data

Conductors for clamping (rated connection)

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

DI 1 :	2.2.25	21	2 2
Blade size	0.6 x 3.5 mm	Clamping range, max.	6 mm²
Clamping range, min.	0.22 mm ²	Clamping screw	M 3
Connection cross-section, stranded	•	Connection cross-section, strande	ed, min.
max.	6 mm²		1.5 mm²
Connection direction	on side	Gauge to IEC 60947-1	A4
Number of connections	2	Stripping length	13 mm
Tightening torque, max.	0.6 Nm	Tightening torque, min.	0.5 Nm
Torque level with DMS electric		Type of connection	
screwdriver	2		Screw connection
Wire connection cross section AWO	3,	Wire connection cross section AV	VG,
max.	AWG 10	min.	AWG 26
Wire connection cross section, fine	у	Wire connection cross-section, fin	iely
stranded, max.		stranded with wire-end ferrules DI	IN

stranded, max.	,	stranded with wire-end ferrules DIN		
	4 mm ²	46228/1, max.	4 mm ²	
Wire connection cross-section, finel stranded with wire-end ferrules DIN 46228/1, min.		Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	4 mm²	
Wire connection cross-section, finel stranded with wire-end ferrules DIN		Wire connection cross-section, finely stranded, min.		
46228/4, min.	0.5 mm ²		0.5 mm ²	
Wire connection cross-section, solic	1	Wire connection cross-section, solid		
core, max.	6 mm²	core, min.	0.5 mm ²	

Display element

Current	6.3 A	Type of voltage for indicator	AC/DC

Fuse terminals

Cartridge fuse	G-Si. 5 x 20	Current	6.3 A
Display	Without LED	Fuse holder (cartridge holder)	Pivoting
Operating voltage, max.	_	Permitted power loss for fuse with	
	250 V	semiconductor protection	
Power loss, 1-pole ; 2-pole ; 3-pole		Type of voltage for indicator	AC/DC

Rating data

Rated cross-section	4 mm ²	Rated voltage	250 V
Rated voltage to adjoining terminal	400 V	Rated current	6.3 A
Current at maximum wires	6.3 A	Standards	IEC 60947-7-3
Volume resistance according to IEC		Rated impulse withstand voltage	
60947-7-x	1 mΩ		6 kV
Pollution severity	3		

UL rating data

Certificate No. (cURus)		Conductor size Factory wiring n	nax.
	E60693	(cURus)	10 AWG
Conductor size Factory wiring	min.	Conductor size Field wiring max	k. (cURus)
(cURus)	22 AWG		10 AWG
Conductor size Field wiring mi	n. (cURus) 22 AWG	Current size B (cURus)	10 A
Current size D (cURus)	10 A	Voltage size B (cURus)	300 V
Voltage size D (cURus)	300 V		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC000899	eClass 6.2	27-14-11-16
eClass 9.0	27-14-11-16	eClass 9.1	27-14-11-16

Approvals

Approvals



Downloads

Approval/Certificate/Document of	
Conformity	Declaration of Conformity
Engineering Data	STEP




Drawings

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

ZQV 4N



Spring connection with PUSH IN Technology

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

delicial	Jideilig data		
Туре	Order No.	GTIN (EAN)	Qty.
ZQV 4N/3	<u>1527940000</u>	4050118332865	60 pc(s).
ZQV 4N/2 BL	<u>1528040000</u>	4050118332773	60 pc(s).
ZQV 4N/4 BL	<u>1528120000</u>	4050118332872	60 pc(s).
ZQV 4N/10	<u>1528090000</u>	4050118332896	20 pc(s).
ZQV 4N/6 BL	<u>1528170000</u>	4050118332926	20 pc(s).
ZQV 4N/4 RD	<u>2460800000</u>	4050118476224	60 pc(s).
ZQV 4N/50	<u>1528240000</u>	4050118333121	5 pc(s).
BL			
ZQV 4N/7	<u>1528020000</u>	4050118332780	20 pc(s).
ZQV 4N/50	<u>2460730000</u>	4050118476156	5 pc(s).
RD			
ZQV 4N/5 BL	<u>1528140000</u>	4050118333015	60 pc(s).
ZQV 4N/5 RD	<u>2460790000</u>	4050118476217	60 pc(s).
ZQV 4N/6	<u>1527990000</u>	4050118332919	20 pc(s).
ZQV 4N/9 RD	<u>2460750000</u>	4050118476170	20 pc(s).
ZQV 4N/8 RD	<u>2460760000</u>	4050118476187	20 pc(s).
ZQV 4N/30	<u>2561600000</u>	4050118569964	5 pc(s).
RD			
ZQV 4N/6 RD	<u>2460780000</u>	4050118476200	20 pc(s).
ZQV 4N/8 BL	<u>1528190000</u>	4050118332858	20 pc(s).
ZQV 4N/50	<u>1528130000</u>	4050118332902	5 pc(s).
ZQV 4N/9	<u>1528070000</u>	4050118332797	20 pc(s).
ZQV 4N/9 BL	<u>1528220000</u>	4050118333107	20 pc(s).
ZQV 4N/7 BL	<u>1528180000</u>	4050118333114	20 pc(s).
ZQV 4N/5	<u>1527980000</u>	4050118332759	60 pc(s).
ZQV 4N/7 RD	<u>2460770000</u>	4050118476194	20 pc(s).
ZQV 4N/30	<u>2561580000</u>	4050118570113	5 pc(s).
ZQV 4N/3 RD	<u>2460810000</u>	4050118476231	60 pc(s).
ZQV 4N/10	<u>1528230000</u>	4050118333138	20 pc(s).
BL			
ZQV 4N/4	<u>1527970000</u>	4050118332889	60 pc(s).
ZQV 4N/2	<u>1527930000</u>	4050118332766	60 pc(s).
ZQV 4N/30	<u>2561610000</u>	4050118569971	5 pc(s).
BL			
ZQV 4N/3 BL	<u>1528080000</u>	4050118333008	60 pc(s).
ZQV 4N/10	2460740000	4050118476163	20 pc(s).
RD			
ZQV 4N/8	<u>1528030000</u>	4050118332841	20 pc(s).
ZQV 4N/2 RD	2460450000	4050118476149	60 pc(s).



ries Weidmüller Interface GmbH & Co. KG Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

ZQV 4N/32 <u>2561670000</u> 4050118570175 5 pc(s).

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	Order No.	Version	GTIN (EAN)	Qty.
DEK 5/6 MC	<u>1609830000</u>	Dekafix, Terminal marker,	400819045660	3 200 pc(s).
SDR		5 x 6 mm, Pitch in mm	mm	
		(P): 6.00 Weidmueller, To		
		customer specification		
DEK 5/6 PLU	S <u>1038650000</u>	Dekafix, Terminal marker,	403224876790	8 200 pc(s).
MC SDR		5 x 6 mm, Pitch in mm		
		(P): 6.00 Weidmueller, To		
		customer specification		



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

WS 12/6



WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

General ordering data

Туре	Order No.	Version	GTIN (EAN)	Qty.
WS 12/6 MM	1 <u>2007200000</u>	WS, Terminal marker, 12 x	405011839188	6 600 pc(s).
WS		6 mm, Weidmueller, white		

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	Order No.	Version	GTIN (EAN)	Oty.
WS 12/6 MC	1773551692	WS, Terminal marker, 12 x	403224814325	2 600 pc(s).
NE BR		6 mm, Pitch in mm (P): 6.0	0	
		Weidmueller, Allen-Bradley	,	
		brown		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

WS 12/6 MC <u>1773551690</u>	WS, Terminal marker, 12 x 4032248143245 600 pc(s).	
NE OR	6 mm, Pitch in mm (P): 6.00	
	Weidmueller, Allen-Bradley,	
	orange	
WS 12/6 MC <u>1773551689</u>	WS, Terminal marker, 12 x 4032248143238 600 pc(s).	
NE VI	6 mm, Pitch in mm (P): 6.00	
	Weidmueller, Allen-Bradley,	
	violet	
WS 12/6 <u>1927530000</u>	WS, Terminal marker, 12 x 4032248574209 600 pc(s).	
PLUS MC NE	6 mm, Pitch in mm (P): 6.00	
WS	Weidmueller, Allen-Bradley,	
	white	
WS 12/6 MC <u>1773551686</u>	WS, Terminal marker, 12 x 4032248141920600 pc(s).	
NE RT	6 mm, Pitch in mm (P): 6.00	
	Weidmueller, Allen-Bradley,	
	red	
WS 12/6 MC <u>1773551687</u>	WS, Terminal marker, 12 x 4032248141937 600 pc(s).	
NE GE	6 mm, Pitch in mm (P): 6.00	
	Weidmueller, Allen-Bradley,	
	yellow	

End brackets



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

Туре	Order No.	Version	GTIN (EAN) Qty.
WEW 35/2	<u>1061200000</u>	W-Series, End bracket	4008190030230100 pc(s).
WEW 35/2	<u>1479000000</u>	W-Series, End bracket	4050118286779 100 pc(s).
V0 GF SW			
WEW 35/2	<u>1859200000</u>	W-Series, End bracket	4032248411658100 pc(s).
GR 7042			
WEW 35/2	<u>1061210000</u>	W-Series, End bracket	4032248136278100 pc(s).
SW			



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	Order No.	Version	GTIN (EAN)	Oty.
DEK 5/6 PL	.US <u>1011320000</u>	Dekafix, Terminal marker,	403224871764	4 1,000 pc(s).
MC NE WS		5 x 6 mm, Pitch in mm (P):	:	
		6.00 Weidmueller, white		

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	Order No.	Version	GTIN (EAN)	Qty.
WS 8/6 PLU	S <u>1951880000</u>	WS, Terminal marker, 8 x 6	6 403224863211	4 600 pc(s).
MC NE WS		mm, Pitch in mm (P): 6.00		
		Weidmueller, white		



WFS 4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	Order No.	Version	GTIN (EAN)	Qty.
DEK 5/6 MC	<u>1912090000</u>	Dekafix, Terminal marker,	4032248540525	5 1,000 pc(s).
NE OR		5 x 6 mm, Pitch in mm (P):		
		6.00 Weidmueller, orange		
DEK 5/6 MC	<u>1609820000</u>	Dekafix, Terminal marker,	4008190203436	6 1,000 pc(s).
NE WS		5 x 6 mm, Pitch in mm (P):		
		6.00 Weidmueller, white		
DEK 5/6 MC	<u>1238290000</u>	Dekafix, Terminal marker,	4050118267327	7 1,000 pc(s).
NE BL		5 x 6 mm, Pitch in mm (P):		
		6.00 Weidmueller, blue		
DEK 5/6 MC	<u>1238280000</u>	Dekafix, Terminal marker,	4050118038750	0 1,000 pc(s).
NE GE		5 x 6 mm, Pitch in mm (P):		
		6.00 Weidmueller, yellow		
DEK 5/6 MC	<u>1238330000</u>	Dekafix, Terminal marker,	4050118323306	6 1,000 pc(s).
NE GR		5 x 6 mm, Pitch in mm (P):		
		6.00 Weidmueller, grey		
DEK 5/6 MC	<u>1238310000</u>	Dekafix, Terminal marker,	4050118271812	2 1,000 pc(s).
NE GN		5 x 6 mm, Pitch in mm (P):		
		6.00 Weidmueller, green		
DEK 5/6 MC	<u>1454900000</u>	Dekafix, Terminal marker,	4050118323313	3 1,000 pc(s).
NE BR		5 x 6 mm, Pitch in mm (P):		
		6.00 Weidmueller, brown		



W-Series

WFS 4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Blank



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Zseries. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Type Order No.	V	ersion G	GTIN (EAN)	Oty.
WS 10/6 MC <u>1828450</u>	<u>000</u> V	/S, Terminal marker, 10 x 4	1032248350513	600 pc(s).
NE WS	6	mm, Pitch in mm (P): 6.00		
	V	/eidmueller, Allen-Bradley,		
	w	hite		
WS 10/6 MC 1917430	<u>000</u> V	/S, Terminal marker, 10 x 4	1032248551637	600 pc(s).
M NE GE	6	mm, Pitch in mm (P): 6.00		
	V	/eidmueller, Allen-Bradley,		
	yı	ellow		
WS 10/6 MC 1069080	<u>000</u> V	/S, Terminal marker, 10 x 4	1032248824618	600 pc(s).
M NE BL	6	mm, Pitch in mm (P): 6.00		
	V	/eidmueller, Allen-Bradley,		
	b	lue		
WS 10/6 <u>1046390</u>	<u>000</u> V	/S, Terminal marker, 10 x 4	1032248782109	600 pc(s).
PLUS MC NE	6	mm, Pitch in mm (P): 6.00		
WS	V	/eidmueller, Allen-Bradley,		
	v	hite		
WS 10/6 M <u>1818400</u>	<u>000</u> V	/S, Terminal marker, 10 x 4	1032248310876	600 pc(s).
MC NE WS	6	mm, Pitch in mm (P): 6.00		
	V	/eidmueller, Allen-Bradley,		
	v	hite		
WS 10/6 MC 1917440	<u>000</u> V	/S, Terminal marker, 10 x 4	1032248551644	600 pc(s).
M NE RT	6	mm, Pitch in mm (P): 6.00		
	V	/eidmueller, Allen-Bradley,		
	re	ed		
WS 10/6 M 2003780	<u>000</u> V	/S, Terminal marker, 10 x 4	4050118424461	600 pc(s).
PLUS MC NE	6	mm, Pitch in mm (P): 6.00		
WS	V	/eidmueller, Allen-Bradley,		
	v	hite		
WS 10/6 MC 1917420	<u>000</u> V	/S, Terminal marker, 10 x 4	1032248551620	600 pc(s).
M NE GN	6	mm, Pitch in mm (P): 6.00		
	V	/eidmueller, Allen-Bradley,		
	g	reen		



WFS 4

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083

www.weidmueller.com

Accessories

Custom printing



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Type Order No.	Version GTIN (EAN) Qty.
WS 10/6 M <u>2007780000</u>	WS, Terminal marker, 10 x 4050118393187 120 pc(s).
PLUS MC SDR	6 mm, Pitch in mm (P): 6.00
	Weidmueller, Allen-Bradley,
	To customer specification
WS 10/6 MC <u>1818410000</u>	WS, Terminal marker, 10 x 4032248310883120 pc(s).
M SDR	6 mm, Pitch in mm (P): 6.00
	Weidmueller, Allen-Bradley,
	To customer specification
WS 10/6 MC <u>1828460000</u>	WS, Terminal marker, 10 x 4032248367399 120 pc(s).
SDR	6 mm, Pitch in mm (P): 6.00
	Weidmueller, Allen-Bradley,
	To customer specification
WS 10/6 <u>1046330000</u>	WS, Terminal marker, 10 x 4032248782031120 pc(s).
PLUS MC SDR	6 mm, Pitch in mm (P): 6.00
	Weidmueller, Allen-Bradley,
	To customer specification



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Test plug



Current and voltage transformer wiring

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General ordering data

Туре	Order No.	Version	GTIN (EAN) Qty.
PS 2.3 RT	0180400000	Accessories, Test plug	400819006012120 pc(s).

Marking Holder



Spring connection with tension clamp Technology

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

Туре	Order No.	Version	GTIN (EAN)	Qty.
BZT 1 WS	<u>1805490000</u>	Accessories, Marker holde	r 403224827023	11 100 pc(s).
10/5				
BZT 1 ZA WS	S <u>1805520000</u>	Accessories, Marker holde	r 403224827024	-8 100 pc(s).
10/5				

End plates



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

Туре	Order No.	Version	GTIN (EAN)	Qty.
WAP 2.5-10	<u>1072210000</u>	W-Series, End plate	400819045546	60 50 pc(s).
M				



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

WAP 2.5-10	<u>1050070000</u>	W-Series, End plate	400819045550750 pc(s).
BR			
WAP 2.5-10	1050000000	W-Series, End plate	4008190103149 50 pc(s).
WAP 2.5-10	1050060000	W-Series, End plate	400819040676950 pc(s).
OR			
WAP 2.5-10	1050080000	W-Series, End plate	400819013661150 pc(s).
BL			
WAP 2.5-10	1050010000	W-Series, End plate	400819040680650 pc(s).
SW			
WAP 2.5-10	1050020000	W-Series, End plate	400819040677650 pc(s).
GE			
WAP 2.5-10	1050090000	W-Series, End plate	400819040679050 pc(s).
WS			
WAP 2.5-10	1050040000	W-Series, End plate	400819040678350 pc(s).
RT			
WAP 2.5-10	1072200000	W-Series, End plate	400819045549150 pc(s).
GN			
WAP 2.5-10	1050050000	W-Series, End plate	400819045548450 pc(s).
GR			

WS 8/6



WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

Туре	Order No.	Version	GTIN (EAN)	Qty.
WS 8/6 MM	2007160000	WS, Terminal marker, 8 x 6 4050118391879600 pc(s).		
WS		mm, Weidmueller, white		



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Custom printing



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	Order No.	Version	GTIN (EAN)	Qty.	
WS 12/6 MC	: <u>1609910000</u>	WS, Terminal marker, 12 x	4008190456658	3 120 pc(s).	
SDR		6 mm, Pitch in mm (P): 6.00			
		Weidmueller, Allen-Bradley,			
		To customer specification			
WS 12/6	<u>1927540000</u>	WS, Terminal marker, 12 x 4032248574711120 pc(s).			
PLUS MC SDR		6 mm, Pitch in mm (P): 6.00			
		Weidmueller, Allen-Bradley	,		
		To customer specification			

Custom printing



WS markers are the perfect match for the W-series connectors. Thanks to their system compatibility, the WS tags can also be used with the I-series and the Z-series. The large marking surfaces do not only permit long character strings but also multi-line text. WS markers are ideal for labels with long, customised character strings. Thanks to the proven MultiCard format, printing with laser printer, PrintJet ADVANCED, plotter or MC-Mobilo is possible.

- · Can be fitted in strips or individually
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	Order No.	Version	GTIN (EAN)	Oty.
WS 8/6 PLUS <u>1038820000</u>		WS, Terminal marker, 8 x 6 4032248768073 120 pc(s).		
MC SDR		mm, Pitch in mm (P): 6.00		



Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Weidmueller, To customer specification

DEK 5/6



WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- · Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

General ordering data

Туре	Order No.	Version	GTIN (EAN)	Qty.
DEK 5/6 MM 2007120000		Dekafix, Terminal marker, 5 4050118392104600 pc(s).		
WS		x 6 mm, Weidmueller, white		

Markers



Extensive range of accessories for the FieldPower® boxes.

Cable seals, plug-in connectors, locking elements and much more.

General ordering data

Туре	Order No.	Version	GTIN (EAN)	Qty.		
WS 12/6 I	MC <u>1609900000</u>	WS, Terminal marke	r, 12 x 40081902034	67 600 pc(s).		
NE WS		6 mm, Pitch in mm (6 mm, Pitch in mm (P): 6.00			
		Weidmueller, Allen-E	Weidmueller, Allen-Bradley,			
V		white	white			
WS 12/6 I	MC <u>1773551688</u>	WS, Terminal marke	WS, Terminal marker, 12 x 4032248141944 600 pc(s).			
NE GN		6 mm, Pitch in mm (6 mm, Pitch in mm (P): 6.00			
		Weidmueller, Allen-E	Weidmueller, Allen-Bradley,			
		green				

Creation date April 9, 2019 9:22:09 AM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 16 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

WS 12/6 MC <u>1773551693</u>

NE BL

WS, Terminal marker, 12 x 4032248143269600 pc(s).

6 mm, Pitch in mm (P): 6.00 Weidmueller, Allen-Bradley,

hlue