


ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00134	Connector, mono plug 3.5xL20.5 mm, brass nickel plated	1	
2	30-00005	Wire, 2C BC, 24 AWG, 300V, 80C, 3.7 mm, shielded, PVC, 76A	1	
3	24-00045	Overmold, PVC, black	1	
4	Heat Shrink	Heat shrink tube, Ø2.0, 30±2 mm, 105°C, black	1	



Wiring diagram	
50-00134	Wire Color
Tip	Red
Ring	Black
N.C.	Shield

Revision:	Date:	Description:	Prepared: GL Digitally signed by GL Date: 2017.02.10 16:48:17 -08'00'	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com
A	1/19/2009	Re-issued CUI spec by Tensility	Verified: PS Digitally signed by PS Date: 2017.02.13 14:41:01 -08'00'	RoHS compliant	
A1	8/21/2009	Added operating and storage temps	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Function test: no open, no short circuit, no intermittent	
A2	8/31/2011	Updated description, connector, and wire information		Description:	
A3	2/10/2017	Updated notes		Cable, 1830 mm, 3.5mm 90° 50-00134 mono plug to stripped tinned, 24 AWG, 30-00005 wire, shielded	
				Size: A	Part number: 053-0276R (CA-2206)
				Scale: 1:1	Sheet 1 of 1