



ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	NOTES
1	50-00008	Connector, 3.5xL26.6 mm, 4C audio plug, brass, nickel plated	1	
2	30-00413	Wire, 4C TC, 26 AWG, 30V, 80C, 3.7 mm, shielded, PVC, 89A	1	
3	24-00075	Overmold, PVC, black	1	



Wiring Diagram	
50-00008	wire color
A	Red
B	Black
C	Yellow
D	Green

Revision:	Date:	Description:	Prepared:	Notes:	TENSILITY tel 1.541.323.3228 800 877.670.7118 fax 1.541.323.4202 web tensility.com		
A1	5/11/2009	Added connector part number	GL Digitally signed by GL Date: 2017.02.10 16:33:32 -08'00'	RoHS compliant			
A2	8/30/2011	Updated description and connector information	Verified: PS Digitally signed by PS Date: 2017.02.13 14:37:02 -08'00'	Function test: no open, no short circuit, no intermittent	Size: A Part number: 053-0113R (CA-354S)		
A3	3/20/2014	Updated description	Dimensions are in millimeters. Tolerances: X: ± 0.5 mm X.X: ± 0.3 mm X.XX: ± 0.05 mm	Description: Cable, 1830 mm, 4C 3.5 mm 50-00008 plug to stripped tinned, 26 AWG, 30-00413			
A4	2/25/2016	Corrected barrel length dimensions					
A5	2/10/2017	Updated notes					

