



ST-200

GRAY
WIRING

TIP - CENTER CONDUCTOR
SLEEVE - SHIELD

22 AWG STRANDED, CENTER
CONDUCTOR, SPIRAL SHIELD,
0.155 OD PVC GRAY

ST-200

GRAY
WIRING

TIP - CENTER CONDUCTOR
SLEEVE - SHIELD

05

A

*

05

X

RoHS COMPLIANT

2ND END - ST-200

CABLE LENGTH PER TABLE BELOW

B = 12 INCHES LONG
C = 18 INCHES LONG
D = 24 INCHES LONG
F = 36 INCHES LONG
H = 48 INCHES LONG
K = 6 FEET LONG
N = 10 FEET LONG
R = 15 FEET LONG
U = 25 FEET LONG

TYPE OF CABLE - W1000 - 1

1ST END - ST-200

NOTES:

1. MATERIALS:
TIP - BRASS, NICKEL PLATED
SLEEVE - BRASS, NICKEL PLATED
INSULATION - PHENOLIC AND POLYESTER
INTERNAL SHIELD - STEEL, TIN PLATED
MOLDED HANDLE - THERMOPLASTIC, GRAY

2. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

						THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.													
					UNLESS OTHERWISE SPECIFIED 1. ALL DIMENSIONS IN INCHES - TWO PLACE DECIMALS ±0.02 - THREE PLACE DECIMALS ±0.005	SIZE		WIDTH		MULT		LBS/M		TEMPER					
						FINISH SPEC No.						MATERIAL SPEC No.							
						FIRST USED ON				SCALE 1:1									
						DATE DRAWN 9-11-06		BY RF	CHKD RF 9-11-06		APVD TJK 8-13-09								
A	26124		8-9-06	JEB		TJK	SHEET 1 OF 1												
REV	ECO NUMBER		DATE	BY		APVD	NAME CABLE ASSEMBLY ST-200 TO ST-200, RoHS						PART No. 05A 05X						REV A
REVISIONS					DO NOT SCALE DRAWING														

SolidWorks CAD File

